

AMENDMENTS TO THE CLAIMS:

The listing of claims will replace all prior versions, and listings of claims in the application:

LISTING OF THE CLAIMS

1. (Original) A wire feeder for an electric arc welder comprising a set of feed rolls driven by a DC motor with a commutator, first and second opposite polarity leads receiving power to drive said motor, and having a first brush at a given position on said commutator and connected to said first lead, a second brush circumferentially spaced from said first brush a first annular distance around said commutator and connectable to said second lead to cause said motor to rotate at a first speed to drive said rolls at a first speed, a third brush circumferentially spaced from said first brush a second annular distance around said commutator and connectable to said second lead to cause said motor to rotate at a second speed to drive said rolls at a second speed, and a switching circuit with an operative condition to connect said second lead to a selected one of said second and third brushes.

2. (Original) A wire feeder as defined in claim 1 wherein said switch circuit is operated manually.

3. (Original) A wire feeder as defined in claim 1 including a controller with a first output signal causing said switch circuit to select said second brush and a second signal causing said switch circuit to select said third brush.

4. (Original) A wire feeder as defined in claim 3 wherein said controller output signal is caused by an input signal indicative of wire size.

5. (Original) A wire feeder as defined in claim 4 wherein said wire feeder includes a fixed ratio gear reducer between said motor and said feed rolls.

6. (Original) A wire feeder as defined in claim 3 wherein said wire feeder includes a fixed ratio gear reducer between said motor and said feed rolls.

7. (Original) A wire feeder as defined in claim 2 wherein said wire feeder includes a fixed ratio gear reducer between said motor and said feed rolls.

8. (Original) A wire feeder as defined in claim 1 wherein said wire feeder includes a fixed ratio gear reducer between said motor and said feed rolls.

9. (Original) A wire feeder as defined in claim 8 wherein said switching circuit when in the condition to select said second brush has a time delay for selecting said third brush for a time before selecting said second brush.

10. (Original) A wire feeder as defined in claim 3 wherein said switching circuit when in the condition to select said second brush has a time delay for selecting said third brush for a time before selecting said second brush.

11. (Original) A wire feeder as defined in claim 2 wherein said switching circuit when in the condition to select said second brush has a time delay for selecting said third brush for a time before selecting said second brush.

12. (Original) A wire feeder as defined in claim 1 wherein said switching circuit when in the condition to select said second brush has a time delay for selecting said third brush for a time before selecting said second brush.

13. (Original) A wire feeder as defined in claim 12 including a circuit to latch said switch circuit in said operative condition when power is received by said leads.

14. (Original) A wire feeder as defined in claim 8 including a circuit to latch said switch circuit in said operative condition when power is received by said leads.

15. (Original) A wire feeder as defined in claim 3 including a circuit to latch said switch circuit in said operative condition when power is received by said leads.

16. (Original) A wire feeder as defined in claim 2 including a circuit to latch said switch circuit in said operative condition when power is received by said leads.

17. (Original) A wire feeder as defined in claim 1 including a circuit to latch said switch circuit in said operative condition when power is received by said leads.

18. (Original) A wire feeder for an electric arc welder comprising a set of feed rolls driven by a motor and a switching condition to change the speed of said motor between a first and second speed.

19. (Original) A wire feeder as defined in claim 18 wherein said switch circuit is operated manually.

20. (Original) A wire feeder as defined in claim 19 wherein when said switching circuit selects said first speed a circuit selects said second speed for a time to accelerate said feed rolls for said time.

21. (Cancelled)

22. (Original) A wire feeder for an electric arc welder comprising a set of feed rolls driven by a D.C motor with a commutator, first and second opposite polarity leads receiving power to drive said motor and having a first brush at a given position on said commutator and connected to said first lead and a second brush circumferentially spaced from said first brush an annular distance around said commutator and connected to said second lead and a device to change the annular distance to change the speed of said motor driving said feed rolls.